

## Fittings / Downlights


# Firestay Protector Open Back Non-Integrated Downlight - White



The Firestay Protector Non Integrated Downlight gives you the freedom to choose your lamp without the need to replace the complete fitting. Available as Fixed, Centre Tilt & IP65 Showerlight with a choice of finishes and accessories.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems.
- Fixed / Centre Tilt / Showerlight IP65 Downlights.
- Part B/C/E compliant.
- Suitable for 240V lamps (GU10 lamp holder included).
- Loop in/out terminals for speed of installation.
- Die-cast aluminium body.
- Part L compliant with BELL Halo Elite/Halo Glass LED GU10.
- Low voltage lampholder available separately (Code 09906).
- One fitting to fit all standard type lamps. Simply choose a BELL lamp for the application required (See LED Lamps section).

## Technical Specification



<b>Product Code</b>	11850
---------------------	-------

### Reference

<b>Guarantee</b>	5 Years
<b>EAN</b>	5013588118505
<b>Commodity Code</b>	9405423990
<b>Country of Origin</b>	CN
<b>UNSPSC Code</b>	39111515

## Technical Specification

Volts (V)	240
IP Rating	IP20

## Dimensions

Height (mm)	77
Length (mm)	135
Diameter (mm)	85
Downlight Cut Out (mm)	72

## Packaging Information

Single Carton Height (mm)	65
Single Carton Width (mm)	107
Single Carton Depth (mm)	92
Single Carton Weight (kg)	0.17
Individual Volume	0.00064
Inner Box Qty	1
Outer Box Qty	50
Outer Box Height (mm)	350
Outer Box Width (mm)	480
Outer Box Depth (mm)	230
Outer Box Weight (kg)	10