



## ALTOLED

Alto Graphite



## Features

Surface bi-directional die-cast wall light providing adjustable beam angle suitable for residential and hospitality applications

Independent beam angle adjustment between up and down distribution

Minimum beam angle 0°, maximum beam angle 90°

Die-cast aluminium body with graphite powder coated anodized paint finish for enhanced durability

Non-dimmable

## General Information

Lamp Type	LED
Colour / Finish	Graphite
IP Rating	IP54
IK Rating	IK05
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L80 50,000h
Warranty (Years)	3
CE Mark	Yes
Width (mm)	79 mm
Height (mm)	172 mm
Depth (mm)	110 mm

# Technical Information

<b>Wattage</b>	6W
<b>Lumens Delivered</b>	320lm
<b>Lm/W</b>	56lm/W
<b>Beam Angle</b>	90
<b>CRI</b>	80
<b>CCT</b>	4000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-20°C to 50°C
<b>SDCM</b>	3

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:06 AM



