

Technical Specification



Description: 2.8mm 5MP Fixed 24/7 IP PoE Bullet Camera







Dimensions (mm)	74 x	75 x 191	Storage Type Micro SD, up to 256 GB	
Finish	White	Enviror	Environment	
Materials	Meta		Ingress Protection	IP67
Weight (Kg)	0.50	0	perating Temperature (°C)	
Warranty (Years)	3		Storage Temperature (°C)	
Supply & Power				
Operating Voltage (V DC) 12			
Power Consumption (W) <1	1.5		
Other Power Sources	Pol	(IEEE802.3af)		
Media Information				
Effective P	ixels	2880 x 1620 (5MP)		
		1/2.7" Progressive CMOS		
Lens size (. ,	·		
Lens				
		112.9 (H), 59.1 (V), 121.2 (D)		
Auto Electronic Shutte				
Speed (s	ec/°)	1 to 1/100000		
		Progressive Scan CMOS		
Frames Per Second (FPS) 30 (@5MP 2880 x 1620)				
Maximum IR Distance	e (m)	n) 30		
IR Wavelength (nm) 850				
	Bit Rate 128 Kbps - 16 Mbps			
Microphone Suppo				
Speaker Suppo				
White Light Range				
		IR-Cut filter with Auto Switch (ICR)		
		Motion Detection, Tampering Alarm, Audio Detection		
Intelligent Deter	ction	Support False Alarm Filtering, Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exit Detection		
Hardware R	leset	No		
Network				
Inter	face	1 RJ45; 10/100M Base-TX Ethernet		
ONVIF Comp	Compliant Yes; Profile S, Profile G, Profile T			
		IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PP HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, S		DDNS, NTP, FTP, UPnP, HTTP,
Supplied Quick St	art Gu	ide, Mounting Guide, Installation Screws an	d Rawlplugs and Pass Throu	gh Gland

Accessories

BBW1: HDVIEW IP 24/7 Bullet Deep Base - White

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com



Page 1 of 1 (14/02/23) Errors & Omissions excluded. Specification is subject to change without notice.