

**Product Code:** HC864R48TB

**Description:** HDview IP 64 Channel 8MP 24/7 48TB Network Video Recorder (NVR)

**General Information**

Dimensions (mm)	426 x 442 x 89
Weight (Kg)	<5.7
Warranty (Years)	3

**Supply & Power**

Operating Voltage (V AC)	100 - 240
Power Consumption (W)	<25

**Inputs & Outputs**

Serial Ports	1 x RS232, 1 x RS485
Alarm Inputs	16
Alarm Outputs	4
Video Input Channels	64
Audio Output Channels (RCA)	1
PoE Standards	IEEE 802.3at & IEEE 802.3af

**Media Information**

Display Video Output	1 x VGA, 2 x HDMI (HDMI Audio is not supported)
Display Split	1, 4, 6, 8, 9, 16, 25 & 36 (VGA) 1, 4, 6, 8, 9, 16, 25, 36 & 64 (HDMI)
Display Resolutions	HDMI1/HDMI2: 4K (3840x2160)(30Hz), 1920x1080p(60Hz), 1920x1080p(50Hz), 1600x1200(60Hz), 1280x1024(60Hz), 1280x720(60Hz), 1024x768(60Hz) VGA: 1920x1080p(60Hz), 1920x1080p(50Hz), 1600x1200(60Hz), 1280x1024(60Hz), 1280x720(60Hz), 1024x768(60Hz)
Sync Playback	16 Channel
Data	RS485

**Network**

Network Connection	2 RJ45 10M, 100M, 1000M self-adaptive Ethernet Interface
Network Functions	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS
USB Interface	2 x USB (2.0), 1 x USB (3.0)

**Supplied** USB Mouse, Quickstart Guide, C13 Mains Cable, Server Mounting Brackets & Screws x 2, Auxiliary Terminal Block x 4

**Compatible Products** Compatible with the range of 24/7 HDview 5MP and 8MP and Rekor IP 2MP Fixed Bullet and Dome Cameras

**Accessories**

 IPIN1POE: 1 Channel POE Injector  
 IPSW4POE: 4 Channel POE Switch  
 IPSW8POE: 8 Channel POE Switch

**Features**

Corridor Mode Screen (3 &amp; 4), FTP, Schedule, Event Screenshots, Supports ONVIF (Profile S, G, T) Cameras, Various fisheye dewarping modes for live view and playback, Supports N+1 Hot spare, Support for 12V Power output