

Technical Specification

Product Code: HDVIP132R8TB

Description: HDview IP PoE 5MP 32CH NVR 8TB





General Information		ording	
Dimensions (mm) 380 x 340 x 50		Maximum Capacity	
Warranty (Years) 3		Ot T	8 Terabytes per SATA connection
Supply & Power			SATA Hard Disk Drive
Operating Voltage (V AC) 110 - 240		Internal HDD	
Power Consumption (mA) <12W		SATA Connection(s)	
Inputs & Outputs			8MP, 5MP, 3MP, 1080p, 720p Manual, Schedule, Alarm
Alarm Inputs 16			Manual, Scriedule, Alarm
Alarm Outputs 1	Envii	ronment	(0.0)
Video Input Channels 32:		Operating Temperature	e (°C) -10 to +50
16 (F	,		
,	igital)		
Audio Output Channels (RCA) 1			
Media Information			
Frames Per Second (FPS)			
Display Video Output			
	1, 4, 6, 8, 9, 10, 10-1, 12, 13, 13-1, 14, 16, 17, 19, 20, 22, 25, 32 & 36		
Display Resolutions	HDMI 1 (Full GUI): 1024x768, 1280x720, 1280x1024, 1440x900, 1920x1080, 3840x2160/EDID		
	HDMI 2 (Limited GUI): 1024x768, 1280x7		
Sync Blayback	VGA (Full GUI): 1024x768, 1280x720, 128 Maximum 16 Channels	50X1024, 1440X900, 1920	08 1000
	Network USB2.0 (Up to 32GB Storage Medium Supported		
·	Yes (Via Password Reset)		
Network	100 (114 1 4000014 110001)		
	01100		
Interface	3 x USB: 1 x USB 2.0 (Front), 1 x USB 3.0		
	1 x USB 2.0 (Rear)		
	1 x RS485		
Network Connection	RJ45; 10/100 BASE-T		
Network Monitoring	Mobile app, Windows & Mac Client, Web Interface		
• "	(0 -) (0 0 1 5 0 0 1 1 (0 -) (-		
Supplied 1 x USB Mous	e (0.5m), 1 x C13 IEC Cable (0.5m), 1 x E	thernet Cable (0.5m)	
Compatible Products HDVIPC: Range	ge of Cameras		
REKIP: Range			
O .	5" LED CCTV Monitor		
	5" LED CCTV Monitor		
	B" LED CCTV Monitor		
WONZSE, 23.0			

Slow Forward (1/2x, 1/4x, 1/8x, 1/16x)

Accessories

Feature

Additional Information Playback Function: Fast Forward & Reverse (2x, 4x, 8x, 16x)

HDVIP1632RRMB: Rack Mount Bracket IPIN1POE: 1 Channel POE Injector IPSW4POE: 4 Channel POE Switch IPSW8POE: 8 Channel POE Switch

Premium Surveillance Hard Disk Drive pre-installed

