DATASHEET



Code: 7G291XLEDITB100

Hartland G2 | HARTLAND G2 RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers


Product Image



۱л	./:	ri	n	$\boldsymbol{\mathcal{L}}$
V	v			u



Dimensions



Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer		
Insert Colour	Antique Brass		
EAN13 Barcode	5051164002893		
Commodity Code	85365015		
Luckins TSI	407518920		
Dimensions(Nominal)	Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm		
Weight	157 GR		
Fixing Hole Centres	Box Fixing = 60.3mm		
Switched Poles	Single		
Current Rating	0.4A		
Voltage	230V AC		
Maximum Load	5-100W (10 LED Lamps MAX)		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Terminal Capacity 1	2X1mm²		
Terminal Capacity 2	2x1.5mm²		
Earth Terminal Capacity 1	5x1mm²		
Earth Terminal Capacity 2	4X1.5mm²		
Earth Terminal Capacity 3	3X2.5mm²		
Earth Terminal Capacity 4	1X4mm² Multi-Strand		
Earth Terminal Capacity 5	1X6mm²		
Product Class 1	Face plate muct be earthed		
Ambient Operating Temperature	-5°C to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
A 4.000 181-1	T ''		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

Additional Notes

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was generated in A/13/2023 12:26:57 PM ESOE.

Trailing Edge & Leading Edge Dimmer