Electrical Speed Controllers

Technical Details

Manrose offer a wide range of variable, 2 speed controllers with reversible options. Consult our technical department for full details.

Fan Speed Controllers - Non Reversible

The variable non-reversing fan speed control is suitable for controlling the speed of fans providing that the electrical load is not less than 20 watts or more than 200 watts. Fits single pattress 20mm deep. A two speed non reversing controller is also available.

Cat. No. Description

1350 Variable fan speed controller **COMTSCV** Variable fan speed controller

1347 Two speed controller (CF400 range only)



1350







1347





1349





1348

METCON

Single phase variable Non Reversible speed controller for use with in-line commercial fans. MAN, MET and MF series. Not suitable for timer models.

Cat. No. Description

METCON Speed controller 1.7amp

Fan Speed Controllers - Reversible

Suitable for WF/XF230/300/COMT/TK/CW/G (except MP models) range. Twin speed and variable speed options available.

Cat. No. Description

1349 Reversible speed controller (variable) **COMTSCVR** Reversible speed controller (variable)

1348 Two speed reversible controller (230mm 9" only).

Humidity Meters

1376

Designed to give a quick and reliable indication of air humidity. Easy to read scale shows the percentage of moisture in air (relative humidity). Electronic maxmin thermometer / hygrometer shows temperature and humidity percentage (relative humidity) on an electronic display and has max-min memory.

Cat. No. Description

1375 Humidity meter

Electronic/digital temperature/

humidity meter





MANROSE