

Technical Specification



Product Code: CMA675 Description: 13A 1 Gang Double Pole Key Lockable Switched Socket With Neon





Earth Plate & Yoke: Mild Steel

General Information

Plate Dimensions (mm) 146 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Rounded Profile Style Finish Polar White Materials Front Plate: Urea

> > Neon Lens: Polycarbonate Terminals: Brass Internal Busbars: Formed Pressed Brass

Terminal Screws: Steel & Yellow Passivated

GridPro Module: GM2018PW

250 Frequency (Hz)

Rated Voltage (V~) (Ue) Resistive Load Rating (A) 13 Termination Type Screw

Anti Microbial Certified

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.2

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

> Modular Rocker Switches Double Pole Switch Yes Twin Earth Terminals Yes

Neon Indicator Yes Indicator Colour Orange

Product Marking On / Off Minimum Back Box Depth (mm) 35

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years)

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Two keys provided (Spare keys available: SP660)

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



E: sales@scolmore.com | W: scolmore.com