

Technical Specification

General Information



Product Code: DPCH655WH

Description: 13A Ingot 1 Gang Double Pole Key Lockable Switched Socket With Neon (Double Plate)





Representative Image

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

146mm (W) x 88mm (H) x 8mm (D) Dimensions **Dimensions With Gasket** 149mm (W) x 91mm (H) x 9mm (D) Plate Design & Finish Rounded Profile Polished Chrome Insert & Gasket Colour White Materials Front Plate: Stainless Steel Insert: Urea 250V~ 50Hz Maximum Voltage Load Rating 13A **Plate Fixing Centres** 120.6mm **Terminal Size** 5mmø **Terminal Torque** 1.2Nm Terminal Capacity 3 x 2.5mm², 2 x 4mm² **Double Pole** Yes Twin Earth Terminals Yes Neon Indicator Yes (Red) **Ingress Protection** IP20 Back Box Depth 35mm Minimum **Operational Temperature** $-5^{\circ}C$ to $+40^{\circ}C$ 10 Years Warranty BS EN 60669-1:1999 +A1:2002 +A2:2008 Standards BS 1363-2: 2016 +A1: 2018 **Additional Information** Two keys provided (Spare keys available: SP660) Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com

Page 1 of 1 Rev.1.3 Errors & Omissions excluded oject to change without notice