

Product Code: GM2018BKMB-DW

Luckinslive 435284776

Description: 20AX Double Pole Switch Module



General Information

| | | |
|--|---|--|
| Dimensions (mm) | 24.5 (W) x 50 (H) x 22.5 (D) | |
| Finish | Matt Black | |
| Insert Colour | Black | |
| Switch Finish | Matt Black | |
| Materials | Body & Insert: Nylon | Switch: Urea |
| | Switch Cover: Stainless Steel | Terminals: Brass |
| | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass |
| Anti Microbial Certified | No | |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Inductive Load Rating (AX) | 20 | |
| Load Rating Comments | Suitable for Fluorescent or Inductive Loads | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) 1.2 |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 | |
| Double Pole Switch | Yes | |
| Product Marking | Dishwasher | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 20 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Patent: GB 2578427



Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | F: +44 (0)1827 63362
E: sales@scolmore.com | W: scolmore.com

