


Product Code: MM002BK

Description: 10AX 2 Way Switch Module



### General Information

<b>Dimensions (mm)</b>	25 (W) x 50 (H) x 22 (D)	
<b>Finish</b>	Black	
<b>Materials</b>	Cover & Housing: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Terminals: Brass Contacts: Silver "on-layer" Copper / Brass
<b>Anti Microbial Certified</b>	No	
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Inductive Load Rating (AX)</b>	10	
<b>Load Rating Comments</b>	Suitable for Inductive Loads	
<b>Termination Type</b>	Screw	
<b>Terminal Size (mm)</b>	Ø5	<b>Terminal Torque Value (Nm)</b> 1.8
<b>Terminal Capacity - Solid (mm²)</b>	4 x 1.5 or 3 x 2.5	
<b>Modular Rocker Switches</b>	Yes	
<b>2 Way Switch</b>	Yes	
<b>Minimum Back Box Depth (mm)</b>	25 (35 Flat Plate)	
<b>Ingress Protection</b>	IP20	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	1	

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.