

## **Technical Specification**

CLICK® ScolmoreGROUP

Product Code: MM022BK Description: 20A Double Pole Switch Module





## **General Information**

 $\textbf{Dimensions (mm)} \quad 25 \text{ (W)} \times 50 \text{ (H)} \times 22 \text{ (D)}$ 

Finish Black

Materials Switch: Urea Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass

Internal Busbars: Formed Pressed Brass

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20
Termination Type Screw

Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 2.5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Modular Rocker Switches Yes

Double Pole Switch Yes

Minimum Back Box Depth (mm) 25 (35 Flat Plate)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 1

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



E: sales@scolmore.com | W: scolmore.com