



Product Code:	MM047BK		Description:	13A Fused Connection Modu	ile		
General Information			Env Low Low Low Low Low Low Low				
) x 04 7 (D)			
Dimensions (mm) Finish		25 (W) x 50 (H Black) x 24.7 (D)				
Materials		Cover & Housing: Polycarbonate Terminals: Brass					
Materialo				Internal Busbars: Fo	rmed Pressed Brass		
Anti Microbial Certified		No					
Rated Voltage (V~) (Ue)		250 Frequency (Hz) 50		50			
Resistive Load Rating (A)		13					
Fuse Fitted Rating & Type		13A (BS 1362)					
Termination Type		Screw					
Terminal Size (mm)		Ø5	Terminal	l Torque Value (Nm)	1.8		
Terminal Capacity - Solid (mm ²)		4 x 1.5 or 3 x 2					
		Fused Symbo	I				
Minimum Back Box Depth (mm)		25 (35 Flat Pla	te)				
Ingress Protection		IP20					
Operational Temperature (°C)		-5 to +40					
Warranty (Years)			1				
Additio	Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.						

UK CA

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com