

Product Code: SFBS142PL

Description: 2 Gang Unfurnished Dimmer Plate- 2 Apertures



General Information

Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Screwless Complete
Finish	Brushed Stainless
Compatible Cover Plate	SCP242#
Materials	Cover Plate: Stainless Steel
	Terminals: Brass
	Earth Strap: Mild Steel
Anti Microbial Certified	No
Minimum Back Box Depth (mm)	35
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	10

Insert: Polycarbonate
Terminal Screws: Steel & Yellow Passivated

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
The safety shutter will only fully open when all three BS 1363 plug-top pins engage correctly with the shutter. Inserting the earth pin alone will not open the live and neutral shutter like conventional socket shutters.

Compatible Dimmer Modules

- MD9014: 100W Dual Mode LED Dimmer Module
- MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module
- MD9010: 1-10V Analogue Rotary Dimmer Module
- MD9022: 40-250W Leading Edge Dimmer Module
- MD9042: 60-400W Leading Edge Dimmer Module

