


Technical Specification



Isolated Satellite & Isolated Coaxial Outlet Product Code: SFBS157BK Description:





General Information

Insert Dimensions (mm) $82.5 \text{ (W)} \times 82.5 \text{ (H)} \times 2.5 \text{ (D)}$ Plate Dimensions (mm) $86 \text{ (W)} \times 86 \text{ (H)} \times 4 \text{ (D)}$

Plate Fixing Centres - Horizontal (mm) 60.3

Style Screwless Complete Finish Brushed Stainless

Insert Colour Black Compatible Cover Plate SCP232#

Materials Cover Plate: Stainless Steel

Insert: Polycarbonate Earth Plate: Mild Steel Terminals: Brass

Anti Microbial Certified No Termination Type Screw **Isolated** Yes

Isolated Comments Enables 1 way signal, reducing signal interference

Non-Isolated No Shielded No Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10 Warranty - Electronics (Years) 1

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram

with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362



