

Technical Specification

CLICK® ScolmoreGROUP

Product Code: SFCHo65PW Description: Single Non-Isolated Coaxial Outlet





General Information

 $\begin{array}{ll} \textbf{Insert Dimensions (mm)} & 82.5 \ (\text{W}) \times 82.5 \ (\text{H}) \times 2.5 \ (\text{D}) \\ \textbf{Plate Dimensions (mm)} & 86 \ (\text{W}) \times 86 \ (\text{H}) \times 4 \ (\text{D}) \\ \end{array}$

Plate Fixing Centres - Horizontal (mm) 60.3

Style Screwless Complete
Finish Polished Chrome
Insert Colour Polar White

Compatible Cover Plate SCP231#

Materials Cover Plate: Stainless Steel

Earth Plate: Mild Steel

Anti Microbial Certified No Termination Type Screw Isolated No

Non-Isolated Yes

Non-Isolated Comments Enables 2 way signal transmission

Minimum Back Box Depth (mm) 25 Ingress Protection IP20 Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Insert: Polycarbonate Terminals: Brass

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms.

PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com



