

Technical Specification

Product Code: SFCH30035PW

Description: 13A 1 Gang Zigbee Smart Switched Socket Outlet & Cover Plate



General Information

Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)	
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Screwless Insert & Cover Plate	
Finish	Polished Chrome	
Insert Colour	Polar White	
Materials	Insert: Polycarbonate	Cover Plate: Stainless Steel
	Rear Housing: Nylon	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass
	Electronics: PCB & Electronic Components	
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	240	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	5.7 x 4.8	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Single Pole Switched	Yes	
3 Pin Safety Shuttered	Yes	
Twin Earth Terminals	No	
		Indicator Colour White & Orange
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	3	
Standards	BS 1363-2 BS EN 61000-6-1 BS EN 61000-6-3 BS EN 60669-2-1 in conjunction with BS EN 60669-1	

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.
3 pin safety shutter. The shutter will only open once all three plug pins are inserted.
Zigbee signal mesh
Enables manual control (unless locked), wireless control and automated control
Voice control via ClickSmart+ Hub using Alexa and/or Google Home