

Product Code: SFCH503BK

Description: 50A Ingot 2 Gang (Vertical) Double Pole Plate Switch With Neon



General Information

| | | |
|--|--|--|
| Insert Dimensions (mm) | 82.5 (W) x 142.5 (H) x 2.5 (D) | |
| Plate Dimensions (mm) | 86 (W) x 1466 (H) x 4 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 120.6 | |
| Style | Screwless Complete | |
| Finish | Polished Chrome | |
| Insert Colour | Black | |
| Compatible Cover Plate | SCP203# | |
| Materials | Cover Plate: Stainless Steel | Insert: Polycarbonate |
| | Rear Housing: Urea | Switch Cover: Stainless Steel |
| | Neon Lens: Polycarbonate | Terminals: Brass |
| | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass |
| | Internal Busbars: Formed Pressed Brass | Earth Strap: Mild Steel |
| Anti Microbial Certified | No | |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 50 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø6 | Terminal Torque Value (Nm) 2.5 |
| Terminal Capacity - Solid (mm²) | 1 x 16 | |
| Double Pole Switch | Yes | |
| Twin Earth Terminals | Yes | |
| Neon Indicator | Yes | Indicator Colour Red |
| Minimum Back Box Depth (mm) | 47 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.