

Technical Specification



Product Code: SFSS060

Description:

ion: 1 Gang Blank Plate



General Information			
Insert Dimensions (mm)		82.5 (W) x 82.5 (H) x 2.5 (D)	
Plate Dimensions (mm)		86 (W) \times 86 (H) \times 4 (D)	
Plate Fixing Centres - Horizontal (mm)		60.3	
Style		Screwless Complete	
Finish		Stainless Steel	
Compatible Cover Plate		SCP060#	
Materials		Cover Plate: Stainless Steel	Insert: Polycarbonate
		Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
		Earth Strap: Mild Steel	
Anti Microbial Certified		No	
Minimum Back Box Depth (mm)		16	
Ingress Protection		IP20	
Operational Temperature (°C)		-5 to +40	
Warranty (Years)		10	
Standards	BS 5733		
	For cleaning / polishing of products, use only a soft, dry, clean cloth. This outlet is not continuously rated and therefore not suitable for use as a permanent charging outlet. CLICK dual voltage shaver outlets incorporate a double wound isolating transformer rated 20Va at 230V or 115V and meets BS EN 61558-2-5:2010 making it safe for use in bathrooms. PTC resettable fuses increase resistance as temperature increases due to increased flow. PTC resettable fuses are designed to limit unsafe currents while allowing constant safe current levels, resistance will "reset" automatically when the fault is removed and temperature returns to a safe level. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.		

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com





