

## **Technical Specification**



Product Code: SFSS158PW		Description:	Single Isolated Coa	axial Outlet	
	0				
General					
Insert Dimensions (mm)		82.5 (W) x 82.	5 (H) x 2.5 (D)		
Plate Dimensions (mm)		86 (W) x 86 (H	H) × 4 (D)		
Plate Fixing Centres - Horizontal (mm)		60.3			
Style		Screwless Co	mplete		
Finish		Stainless Stee	J		
Insert Colour		Polar White			
Compatible Cover Plate		SCP231#			
Materials		Cover Plate: S	itainless Steel	Insert: Polycarbonate	
		Earth Plate: M	ild Steel	Terminals: Brass	
Anti Microbial Certified		No			
Termination Type		Screw			
Isolated		Yes			
Isolated Comments		Enables 1 way signal, reducing signal interference			
Non-Isolated		No			
Shielded		No			
Minimum Back Box Depth (mm)		25			
Ingress Protection		IP20			
Operational Temperature (°C)		-5 to +40			
Warranty (Years)		10		Warranty - Electronics (Years)	1
Additional Informa	Ensure th with the r Bare eart Isolated s	For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.			

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarmworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com



