

Technical Specification

Product Code: SFSS30036GY

Description: 13A 2 Gang Zigbee Smart Switched Socket Outlet & Cover Plate



General Information

| | | |
|--|--|--|
| Insert Dimensions (mm) | 142.5 (W) x 82.5 (H) x 2.5 (D) | |
| Plate Dimensions (mm) | 146 (W) x 86 (H) x 4 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 120.6 | |
| Style | Screwless Insert & Cover Plate | |
| Finish | Stainless Steel | |
| Insert Colour | Grey | |
| Materials | Insert: Polycarbonate | Cover Plate: Stainless Steel |
| | Rear Housing: Nylon | Terminals: Brass |
| | Terminal Screws: Steel & Yellow Passivated | Internal Busbars: Formed Pressed Brass |
| | Electronics: PCB & Electronic Components | |
| Anti Microbial Certified | No | |
| Rated Voltage (V~) (Ue) | 240 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 13 | |
| Termination Type | Screw | |
| Terminal Size (mm) | 5.7 x 4.8 | Terminal Torque Value (Nm) 1.2 |
| Terminal Capacity - Solid (mm²) | 3 x 2.5 or 2 x 4 | |
| Single Pole Switched | Yes | |
| 3 Pin Safety Shuttered | Yes | |
| Twin Earth Terminals | Yes | |
| | | Indicator Colour White & Orange |
| Minimum Back Box Depth (mm) | 35 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 3 | |
| Standards | BS 1363-2 BS EN 61000-6-1 BS EN 61000-6-3 BS EN 60669-2-1 in conjunction with BS EN 60669-1 | |

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.
3 pin safety shutter. The shutter will only open once all three plug pins are inserted.
Zigbee signal mesh
Enables manual control (unless locked), wireless control and automated control
Voice control via ClickSmart+ Hub using Alexa and/or Google Home